



# AUTOMATIC FLUSH VALVE



## PART NUMBER

AFV  
AFV-KIT

## AFV-KIT Includes:

- (2) 1/2" Barb x 1/2" NPT male hose fittings
- (2) SAE size 8 SS worm drive clamps
- (24") 1/2" braid reinforced flexible PVC tubing. (rated at 215 PSI)

**Kit does not include filter or automatic flush valve.**

**Please note:** To insure optimum performance of automatic flush valve, it is recommended that you use the above rated tubing only.

## SPECIFICATIONS

Adjustable cycle time.....5 min. - 24 hours  
 Working Pressure .....200 PSIG  
 Ambient Temperature.....35°F to 165°F  
 Enclosure.....Nema 4  
 Voltage .....115V, 1 Phase, 60HZ  
 Current.....2.5 Amps  
 Valve Construction.....Brass  
 Seals .....Reinforced Teflon  
 Discharge Volume.....1/2" NPT-.92  
 (Gal per cycle @ 30 PSIG)  
 Power cord.....8 ft. heavy-duty grounded  
 Full-Port Ball Valve .....1/2" NPT  
 Discharge Time.....3.5 seconds  
 (Non-Adjustable)

**Phone: 352-597-2522**  
**Toll Free 1-800-345-1033**  
**Fax: 352-596-9489**  
**Email: info@rusco.com**

## SUGGESTED INSTALLATION

